

No. 0470 **KOCH Ecoprimer Silikatgrund**  
**KOCH Ecoprimer Silicate Primer**



No. 0407 **KOCH Ecoprimer FixAtiv**

**Technical Data Sheet**

Article No. 0470, 0331, 0962 - . 0964, 0471, 0407-0408 Date 15.08.2014, Page 1  
 - 2, EN

**Application**

- Primer for subsequent coatings with lime paints, silicate paints and plasters
- good adhesion for coatings
- consolidate, neutralize, shut off
- compensation equal absorbent substrate
- for mineral-absorbent surface
- extend of silicate paints, plaster
- isolate resounding underground
- Creating glazes

**Suitable for:**

Residential premises, Warehouses, listed buildings, hospitals, nursing homes, kindergartens, schools.

Others		System	Lime + silicate system
For processing	ready	Process	rolling, brushing, airless
Creating plots:	compellingly	Drying time	12 Hours
Working temperature:	+ 10 ° C	Consumption	0.20 liters - 0.25 liters / sqm..
Storage:	Frost Free	Transport Plate	eliminates
Classification according to	does not require labeling	Waste code no.	(EAKV 2002): 31442
EC Waste Code	No. 31442	Cleaning tools	Water
Oily Substrates	not suitable	Material Safety Data Sheet:	note
before use	stir vigorously with whisk	Use	not intended for human consumption
Thin	Water up to 5%	Density	ca. 1,15g / ml
Paintings	1 x	PH value	approximately 11.5
Customs tariff number	38249070	Solvent / VOC	0%
Plastic dispersion	0%	Best before [date:	9 months, cooling, frost-free conditions

Surface must be: sound, clean, dry, without wax without silicone, without dust (see VOB) primer:

**Airless Applications**

See: Airless Technical Data Sheet

**Suitable for:**

Residential premises, Warehouses, listed buildings, hospitals, nursing homes, kindergartens, schools.

Product	Interior	Outdoors	Hue
No. 0470 KOCH Ecoprimer Silicate Primer	X	X	Transparent
No. 0407 KOCH Ecoprimer FixAtiv	X	X	Transparent

Suitable for:	No. 0470 KOCH Ecoprimer Silicate Primer	No. 0407 KOCH Ecoprimer FixAtiv
Before coating with: silicate paints and plasters, lime paints and plasters, clay paints and plasters.	X	X
On old coatings: lime paints, silicate paints, lime plaster, cement plaster, gypsum plaster, plasterboard, lime cement, silicate plasters, clay plasters. etc.	X	X

Product	Crumbling underground	Extend of silicate paints / plasters
No. 0470 KOCH Ecoprimer Silicate Primer		
No. 0407 KOCH Ecoprimer FixAtiv	X	X

**Not suitable on:**

Latex paint, poorly absorbent substrates

**Processing to third-party products / use of third-party products**

Because of the variety of products on the market own tests must be carried out by the processor to assess the compatibility with other products. Mixing with products that are alien to the system is not permitted! The same goes for Koch paint Factory products that are not part of lime or silicate system.

### Composition (All ingredients )

Mixture of water glass, water, vegetable emulsifier, accompanied by a variety of biological, mineral adjuvants, (without plastic dispersion, solvents)

### Identification

Lovely	Xi	Irritant to skin	R38
Risk eye damage	S2	Do not give to children.	S 24/25
Touch eyes, avoid skin	S 26	Avoid contact with eyes, rinse immediately with water and seek medical visit.	S 36/37/39
When working	Protective clothing, protective gloves, safety goggles, face protection.		

### Safety note

Covering: z. As glass, ceramics, wood, paint, brick, metal, etc.

Information describes exclusively technical characteristics of the product / products. To the best of our knowledge. Offers no assurance of properties within the meaning of the legal warranty regulations. Delivery specifications refer. The technical information has been prepared in accordance with the European legislation.

### Technical Information Sheet, Issuing Company: Contact person:

Koch GmbH · Mörikestraße 23 · D74632 Neuenstein

Tel. (+49) 07942-941322

Email: kontakt@koch-farbenwerk.de · Internet www.koch-farbenwerk.eu